



TITANIUM MOUNTAIN BIKE SPRINGS

1.38" I.D. x 2.50" STROKE

FITS FOX DHX, MRP & ELKA STAGE 5 SHOCKS

PART #	I.D.	O.D.	WT.(lb)	FREE LENGTH	RATE
SCT-138-052-0350	1.38"	2.06"	0.56	5.200"	350
SCT-138-054-0400	1.38"	2.10"	0.66	5.400"	400
SCT-138-054-0450	1.38"	2.12"	0.69	5.400"	450
SCT-138-057-0500	1.38"	2.16"	0.82	5.700"	500
SCT-138-057-0550	1.38"	2.18"	0.86	5.700"	550

1.38" I.D. x 2.75" STROKE

FITS FOX DHX, MRP & ELKA STAGE 5 SHOCKS

PART #	I.D.	O.D.	WT.(lb)	FREE LENGTH	RATE
SCT-138-057-0350	1.38"	2.10"	0.62	5.700"	350
SCT-138-057-0400	1.38"	2.12"	0.66	5.700"	400
SCT-138-059-0450	1.38"	2.16"	0.79	5.900"	450
SCT-138-060-0500	1.38"	2.18"	0.82	6.000"	500
SCT-138-060-0550	1.38"	2.20"	0.86	6.000"	550

1.38" I.D. x 3.00" STROKE

FITS FOX DHX, MRP & ELKA STAGE 5 SHOCKS

PART #	I.D.	O.D.	WT.(lb)	FREE LENGTH	RATE
SCT-138-063-0300	1.38"	2.10"	0.70	6.300"	300
SCT-138-065-0350	1.38"	2.12"	0.74	6.500"	350
SCT-138-065-0400	1.38"	2.16"	0.87	6.500"	400
SCT-138-067-0450	1.38"	2.20"	1.01	6.700"	450
SCT-138-071-0550	1.38"	2.26"	1.22	7.100"	550

1.43" I.D. x 2.25" STROKE

FITS DVO, BOS STOV, MANITOU, MARZOCCHI, CANE CREEK, X-FUSION, & OHLINS SHOCKS

PART #	I.D.	O.D.	WT.(lb)	FREE LENGTH	RATE
SCT-143-053-0350	1.43"	2.09"	0.72	5.300"	350
SCT-143-053-0450	1.43"	2.09"	0.86	5.300"	450

1.43" I.D. x 2.50" STROKE**FITS DVO, BOS STÖY, MANITOU, MARZOCCHI, CANE CREEK, X-FUSION, & OHLINS SHOCKS**

PART #	I.D.	O.D.	WT.(lb)	FREE LENGTH	RATE
SCT-143-053-0250*	1.43"	2.04"	0.68	5.300"	250
SCT-143-053-0300*	1.43"	2.04"	0.70	5.300"	300
SCT-143-053-0350*	1.43"	2.09"	0.72	5.300"	350
SCT-143-053-0450*	1.43"	2.09"	0.86	5.300"	450
SCT-143-058-0550	1.43"	2.27"	1.12	5.800"	550
SCT-143-058-0600	1.43"	2.29"	1.18	5.800"	600

1.43" I.D. x 2.75" STROKE**FITS DVO, BOS STÖY, MANITOU, MARZOCCHI, CANE CREEK, X-FUSION, & OHLINS SHOCKS**

PART #	I.D.	O.D.	WT.(lb)	FREE LENGTH	RATE
SCT-143-063-0450	1.43"	2.21"	1.19	6.300"	450
SCT-143-063-0500	1.43"	2.25"	1.19	6.300"	500
SCT-143-063-0550	1.43"	2.25"	1.24	6.300"	550
SCT-143-063-0600	1.43"	2.29"	1.30	6.300"	600

1.43" I.D. x 3.00" STROKE**FITS DVO, BOS STÖY, MANITOU, MARZOCCHI, CANE CREEK, X-FUSION, & OHLINS SHOCKS**

PART #	I.D.	O.D.	WT.(lb)	FREE LENGTH	RATE
SCT-143-066-0450	1.43"	2.21"	1.14	6.600"	450
SCT-143-066-0500	1.43"	2.25"	1.19	6.600"	500

PROGRESSIVE 5TH ELEMENT SPRING SPACER

All springs with part numbers followed with an asterisk (*) will require one spacer when used on a Progressive 5th Element Shock. This is due to the shock not having as much thread length as other shocks which limits the variation in spring length it will accommodate. Spacers are sold separately and are not included with any springs. Made from UHMW plastic for minimal weight.

PART #	I.D.	O.D.	COLOR
RCU-126-140	1.26"	1.85"	BLACK

1.50" I.D. x 2.50" STROKE**FITS ROCK SHOX VIVID & KAGE SHOCKS**

PART #	I.D.	O.D.	WT.(lb)	FREE LENGTH	RATE
SCT-150-060-0350	1.50"	2.25"	0.76	6.000"	350
SCT-150-062-0450	1.50"	2.30"	0.91	6.200"	450
SCT-150-063-0500	1.50"	2.34"	1.03	6.300"	500

1.50" I.D. x 2.75" STROKE**FITS ROCK SHOX VIVID & KAGE SHOCKS**

PART #	I.D.	O.D.	WT.(lb)	FREE LENGTH	RATE
SCT-150-060-0350	1.50"	2.25"	0.76	6.000"	350
SCT-150-062-0450	1.50"	2.30"	0.91	6.200"	450
SCT-150-063-0500	1.50"	2.34"	1.03	6.300"	500

1.50" I.D. x 3.00" STROKE**FITS ROCK SHOX VIVID & KAGE SHOCKS**

PART #	I.D.	O.D.	WT.(lb)	FREE LENGTH	RATE
SCT-150-064-0400	1.50"	2.28"	0.89	6.400"	400
SCT-150-067-0450	1.50"	2.33"	1.05	6.700"	450



425 S 7th St. Renton, WA 98055
p 425.255.1453 f 425.228.0780
www.rentoncoilsspring.com